



# LINEAR-EVO-FLY

	LINEAR-EVO-FLY 600MM	LINEAR-EVO-FLY 1200MM
<b>ALIMENTAZIONE / POWER SUPPLY</b>	98-264Vac	
<b>POTENZA MASSIMA ASSORBITA MAXIMUM POWER INPUT</b>	35W	70W
<b>SORGENTE / SOURCE</b>	SMD LED	
<b>COLORE LUCE / LIGHT COLOR</b>	Ciano / Cyan con sistema integrato dissuasione volatili / with integrated system for bird dissuasion	
<b>TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE</b>	Da/From -20°C a/to +50°C	
<b>CONTROLLO / CONTROL</b>	On / Off	
<b>MATERIALI MATERIALS</b>	<ul style="list-style-type: none"><li>• Alluminio anodizzato (struttura) / Anodized aluminum (structure)</li><li>• Acciaio verniciato (staffa) / Painted steel (bracket)</li><li>• Acciaio inox (viteria e pressacavi) / Steel (screws and cable glands)</li><li>• Vetro temprato 4 mm (schermo) / Tempered glass 4 mm (closure)</li><li>• Silicone (guarnizioni) / Silicone (gaskets)</li></ul>	
<b>GRADO DI PROTEZIONE IP IP PROTECTION CLASS</b>	IP65	
<b>PESO / WEIGHT</b>	5 kg	8,5 kg
<b>DIMENSIONI IMBALLO PACKAGING DIMENSIONS</b>	750 mm (L) x 150 mm (W) x 150 mm (H)	1500 mm (L) x 150 mm (W) x 150 mm (H)
<b>DIMENSIONI LAMPADA LAMP DIMENSION</b>	630 mm (L) x 142 mm (W) x 100 mm (H)	1262 mm (L) x 142 mm (W) x 100 mm (H)

